



EC5SAW SERIES

10 WATT WIDE INPUT DC-DC CONVERTERS



FEATURE

- * 4:1 Input Range
- * Regulated Outputs
- * 3000VDC/2000VAC Isolation
- * Efficiency Up to 89.5%
- * Compact SIP8 Package
- * Remote On/Off Control
- * 6.6-10W Isolated Output
- * Fixed Switching Frequency
- * No Tantalum Capacitor Inside
- * Input Under-Voltage Protection
- * Low No Load Power Consumption
- * Continuous Short Circuit Protection



MODEL NUMBER	INPUT VOLTAGE(4)	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT		%EFF.		CAPACITOR LOAD MAX.
			MIN.	MAX.	NO LOAD	FULL LOAD	(3)	(2)	
EC5SAW-24S33N	9-36 VDC	3.3 VDC	0 mA	2000 mA	6 mA	336 mA	81	81.5	2000uF
EC5SAW-24S05N	9-36 VDC	5 VDC	0 mA	2000 mA	6 mA	490 mA	83.5	85	2000uF
EC5SAW-24S12N	9-36 VDC	12 VDC	0 mA	833 mA	6 mA	473 mA	87	89	833uF
EC5SAW-24S15N	9-36 VDC	15 VDC	0 mA	666 mA	6 mA	468 mA	88.5	89.5	666uF
EC5SAW-24D05N	9-36 VDC	±5 VDC	0 mA	±1000 mA	6 mA	490 mA	84	85	1000uF
EC5SAW-24D12N	9-36 VDC	±12 VDC	0 mA	±417 mA	7 mA	468 mA	88.5	89	417uF
EC5SAW-24D15N	9-36 VDC	±15 VDC	0 mA	±333 mA	7 mA	468 mA	88.5	89	333uF
EC5SAW-48S33N	18-75 VDC	3.3 VDC	0 mA	2000 mA	6 mA	168 mA	81	81	2000uF
EC5SAW-48S05N	18-75 VDC	5 VDC	0 mA	2000 mA	6 mA	245 mA	84	85	2000uF
EC5SAW-48S12N	18-75 VDC	12 VDC	0 mA	833 mA	6 mA	237 mA	87.5	88	833uF
EC5SAW-48S15N	18-75 VDC	15 VDC	0 mA	666 mA	6 mA	234 mA	87.5	88	666uF
EC5SAW-48D05N	18-75 VDC	±5 VDC	0 mA	±1000 mA	6 mA	245 mA	84	85	1000uF
EC5SAW-48D12N	18-75 VDC	±12 VDC	0 mA	±417 mA	6 mA	234 mA	88	88	417uF
EC5SAW-48D15N	18-75 VDC	±15 VDC	0 mA	±333 mA	6 mA	234 mA	87.5	88	333uF

NOTE:

1. Nominal Input Voltage 24 or 48 VDC
2. Measured at Nominal Input Voltage
3. Measured at 12VDC for 24Vin, 24VDC for 48Vin
4. For 3.3Vo, 5Vo & ±5Vo has Derating by Input is Required Show Fig.1

SPECIFICATIONS

All Specifications Typical At Nominal Line, Full Load, and 25°C Unless Otherwise Noted


INPUT SPECIFICATIONS:

Input Voltage Range	24V	9-36V
	48V.....	18-75V
Input Surge Voltage (100 ms max.)	24V	50VDC max.
	48V.....	100VDC max.
Input Filter		Capacitive
Remote On/Off Control:		
Module On		Open or High Impedance
Module Off		2mA to 4mA
Module Off (Input Idle Current)		2.5mA max.

OUTPUT SPECIFICATIONS:

Voltage Accuracy	$\pm 1.0\%$ max.
Voltage Balance (Dual)	$\pm 1.0\%$ max
Transient Response: 75%~100% Step Load Change	
Error Band	$\pm 5\%$ Vout Nominal, Recovery Time
Ripple & Noise, 20MHz BW (Note 5)	3.3V & 5V & $\pm 5V$... 100mV pk-pk max.
	12V/15V/ $\pm 12V/\pm 15V$ 1%Vo max.
Temperature Coefficient	$\pm 0.02\%/^{\circ}\text{C}$ max.
Short Circuit Protection	Continuous
Line Regulation (note1)	$\pm 0.2\%$ max.
Load Regulation (note2)	$\pm 1.0\%$ max.
Cross Regulation (Dual note3) ...	Asymmetrical Load 25%/100% .. $\pm 5.0\%$ max.
Current Limit	180% typ.
Start up time	5ms typ.

CASE SA DIMENSIONS:



PIN CONNECTION		
Pin	Single	Dual
1	-V Input	-V Input
2	+V Input	+V Input
3	On/Off	On/Off
6	+V Output	+V Output
7	-V Output	Common
8	NC	-V Output

GENERAL SPECIFICATIONS:

Efficiency	See Table
Isolation Voltage	Input/Output 3000VDC min.
	Input/Output 2000VAC min.
Isolation Resistance	10^9 ohm min.
Isolation Capacitance	50pF max.
Switching Frequency	530KHz typ.
Operating Ambient Temperature	-40°C to +85°C
De-rating, Above 50°C	Linearly to Zero power at 105°C
Case Temperature (note4)	105°C max.
Cooling	Natural Convection
Storage Temperature	-55°C to +125°C
Humidity	95% RH max. Non condensing
MTBF	MIL-HDBK-217F, GB, 25°C, Full Load 1930Khrs typ.
Dimensions	0.87x0.37x0.47 inches (22.0x9.5x12.0mm)
Case Material	Non-Conductive Black Plastic
Weight	4.9g

NOTE:

1. Measured from high line to low line.
2. Measured from full load to no load.
3. For asymmetric loading, both channels must be at 25% load or more.
4. Maximum case temperature under any operating condition should not be exceeded 105°C.
5. Output ripple and noise measured with 1uF ceramic capacitor




Fig1. Input Voltage Derating Curve
Typical Derating curve for Natural Convection




Fig2. Typical Derating Curve for Naturel Convection